QUICK START

Wireless release transmitter

sp-wrb_mini · on the field

SHOOMS

QS-WT-EN · 09.2026

BEFORE YOU START

The transmitter is installed after the receivers on the traps are mounted. Only SHOOMS staff open the enclosure.

INSTALLATION STEPS

1. Fix the transmitter's enclosure in the chosen place; the enclosure must not move.
2. Screw the antenna fully onto the SMA connector and position it vertically.
3. Connect the power supply to the «12V» socket, then plug it into a 230 V socket.
4. Check with a SHOOMS specialist that the transmitter has appeared on the range network.
5. Test the release of every trap fitted with a wireless receiver.
6. Compare the result with the installation log: exactly that trap must fire.

BEFORE YOU LEAVE

- [ ] Enclosure fixed, antenna vertical
- [ ] Power connected
- [ ] Transmitter visible on the range network
- [ ] Every wireless trap tested
- [ ] Installation log filled in
- [ ] Serial number recorded

IF SOMETHING DOES NOT WORK

No trap fires	The transmitter's power: the socket, the power supply, the «12V» plug
Power is on, the traps stay silent	The range router; power the transmitter down for 10 s and back on
One trap does not work	The receiver on that trap — see its quick start
Release is intermittent	The transmitter's antenna and the distance to the farthest trap

The full user manual is in the documentation set or behind the QR code. SHOOMS support: support@shooms.net